

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (currently amended): Method for manufacturing non-contaminated MOX fuel rods ~~(1)~~, from pellets ~~(6)~~, in a containment enclosure ~~(10)~~ under a depression, the method comprising the following operations for one rod ~~(1)~~:
 - loading of the pellets ~~(6)~~ in successive columns ~~(12)~~ into a cladding ~~(2)~~ previously provided with a first plug ~~(3)~~ at one of its two ends;
 - loading of various structural components, ~~in particular including~~ a retaining spring ~~(7)~~;
 - fitting of a second plug ~~(4)~~ at the other end of the cladding ~~(2)~~;
 - peripheral welding of said second plug ~~(4)~~, ~~in particular if it is not fitted with tightening in said cladding (2); and~~
 - at least one cleaning and at least one checking of ~~the~~ contamination of the parts of said cladding ~~(2)~~ or respectively of the rod ~~(1)~~ which have been exposed to contamination, the method being characterised in that it comprises:
 - division of the containment enclosure ~~(10)~~ into a number of successive compartments;
 - connection of each compartment to its neighbour for a tight passage for the cladding ~~(2)~~, at least certain of said passages being aligned in order to allow a movement of the cladding ~~(2)~~ along a longitudinal axis;

- introduction of the cladding (2) to be loaded, ~~said other~~the open end (34) in front, into a first compartment through a sealed passage or an input aperture thereto;
- axial driving of the cladding (2) between successive compartments until ~~said other~~its open end (34) reaches the last compartment;
- loading of the pellets (6) in the last compartment, and if applicable also various structural components (5) other than the retaining spring (7), into the cladding (2) through ~~said other~~ its open end (34);
- partial axial withdrawal of the cladding (2), when the loading is finished, so as to convey ~~said other~~its open end (34) into a preceding compartment;
- in this preceding compartment, cleaning and a possible contamination check of at least the part of the cladding (2) exposed to contamination by the pellets (6) in the process of being loaded or by the atmosphere of the last compartment;
- after this cleaning, axial movement of the cladding (2) so that ~~the open end area~~~~said other end~~ (34) is positioned in another compartment;
- loading of the retaining spring (7) and fitting of the second plug (4) in ~~the open~~~~said other~~ end (34), in this other compartment;
- after this fitting, carrying out of possible other operations in the same compartment or in yet another compartment, with a possible additional movement;
- contamination checking of the parts of the rod (1) exposed to the contamination of the last compartments and possible cleaning if necessary, in the first or the second compartment;

- withdrawal of the rod ~~(1)~~ out of the first compartment or a transverse transfer to another containment enclosure via a first compartment connecting the enclosures to one another;
- stepping of the contaminations between the various compartments, starting from the non-contaminated or the very slightly contaminated in the first compartment to the most contaminated in the last compartment;
- selection of gases supplying the compartments, chosen from amongst the group formed by: air, nitrogen, helium, argon, vacuum;
- stepping of ~~the~~ depressions in the compartments, in order to organise any leaks, from ~~the a~~ weakest depression in the first compartment to ~~the a~~ strongest depression in the last compartment.

2. (currently amended): Method according to Claim 1, characterised in that, for loading of the pellets ~~(6)~~ and the following associated operations:

- presenting, centring and aligning the pellets ~~(6)~~ of a column ~~(12)~~ from a support ~~(38)~~ to ~~the opensaid other end (34) of the cladding (2); and~~

the following are performed:

- correction of off-centrings between the support ~~(38)~~ and ~~the opensaid other end (34) of~~ the cladding ~~(2)~~, and alignment of the axis of the pellets ~~(6)~~ with the axis of the cladding ~~(2)~~, by means of a channel ~~(42)~~, the bottom of which has a V-shaped profile in a continuous ramp and intersecting with a cylindrical output with the diameter of the pellets ~~(6)~~;
- centring of the cladding ~~(2)~~ in a chamber centred on the cylindrical part of the channel;

- masking of the ~~open~~said other end ~~(34)~~ of the cladding ~~(2)~~ from the pellets ~~(6)~~ in the process of being loaded;

- trapping and/or collection and/or forcing back of dust and chips conveyed by and/or adhering to the pellets ~~(6)~~ loaded, and/or generated by the presentation, centring and alignment operations, via ~~the~~ free sections between pellets ~~(6)~~ and walls of the channel and/or grooves, by gravity deposition and optionally by additional blowing and/or suction.

3. (currently amended): Method according to Claim 2, characterised by loading of the pellets ~~(6)~~ of a column into the cladding ~~(2)~~, to a depth of introduction of the last pellet ~~(6)~~ in the cladding ~~(2)~~ equal to at least the length of the next column to be loaded into the same cladding ~~(2)~~.

4. (currently amended): Method according to Claim 3, characterised in that loading of said pellets ~~(6)~~ in successive columns into said cladding ~~(2)~~ is performed by limiting the maximum pushing forces during loading, according to the depth of introduction of ~~the a~~ pushing device and the order ~~(N)~~ of the column in the process of being loaded into the same cladding ~~(2)~~.

5. (currently amended): Method according to Claim 4, characterised by a dry or slightly moist process for cleaning the parts of the cladding ~~(2)~~, or respectively of the rod ~~(1)~~, exposed to contamination, this process possibly being by rubbing.

6. (currently amended): Method according to Claim 5, characterised in that the enclosure is divided into four compartments ~~(I-IV)~~, of which

- the fourth and last compartment ~~(IV)~~ is intended for loading of the pellets ~~(6)~~ and structural elements;

- the third ~~(III)~~ is intended for cleaning of the part exposed to contamination during loading;

- the second ~~(II)~~ is intended for loading of the spring ~~(7)~~ and fitting of the second plug ~~(4)~~, and possible girth welding thereof if the fitting is not with tightening; and

- the first ~~(I)~~ is intended for contamination checking and possible cleaning of the parts exposed to contamination in the preceding compartments, and for input of the cladding and output of the rod.

7. (currently amended): Method according to Claim 6, characterised in that

- loading of the pellets ~~(6)~~, cleaning of the end of the cladding ~~(2)~~ exposed to contamination and fitting of the second plug ~~(4)~~ are performed in compartments under helium, as well as optionally ~~the contamination measurement at the output~~ said contamination check;

- upon introduction of a cladding ~~(2)~~ empty of pellets into the containment enclosure ~~(10)~~, ~~its open~~ said other end ~~(34)~~ is transferred into the first compartment under helium encountered only after pumping out and replacement, between this compartment and the preceding one, of the gas contained in the cladding ~~(2)~~ with helium.

8. (currently amended): Method according to Claim 6, characterised in that

- loading of the pellets ~~(6)~~ is performed in the last compartment under vacuum or in an enclosure under vacuum located therein; and

- upon introduction of a cladding ~~(2)~~ empty of pellets ~~(6)~~ into the containment enclosure ~~(10)~~, its open end ~~(34)~~ is transferred into this last compartment only after pumping out, between this compartment and the preceding one, of the gas contained in the cladding ~~(2)~~.

9. (currently amended): Device for manufacturing non-contaminated MOX fuel rods (1) from pellets (6), for implementation of the method according to Claim 1, and comprising a containment enclosure (10) for carrying out the following operations:

- loading of the pellets (6) in columns (12) into a cladding (2) open at one end and closed by a first plug (3) at the other;

- cleaning and possible checking of the contamination of the part of said cladding (2) which has been brought into contact with contamination or dust from said pellets (6);

- loading of various structural components, ~~in particular~~ including a retaining spring (7);

- fitting of a second plug (4);

- checking of ~~the~~ a contamination and ~~possible~~ possibly cleaning of the part of said cladding (2) which has been brought into contact with contamination,

~~the device being characterised in that~~ wherein:

- the containment enclosure (10) is divided into a number of distinct compartments;

- the compartments are preferentially in succession one after the other in a direction of movement between compartments of a cladding (2) to be loaded, ~~the open~~ said other end (34) in front;

- the compartments of the enclosure are isolated from one another by sealed partitions having, for passing the cladding (2) from one compartment to another, a tight passage (24), itself consisting of a full-passage valve (26) and a sealing device (28) on the circumference of the cladding (2), at least certain of said passages (24) being aligned in the direction of movement of

the above-mentioned cladding (2), the first compartment encountered possibly being simply provided with an aperture at its input;

- at least one axial driving mechanism is arranged in order to move along its longitudinal axis the end of the introduced cladding (2) or of the rod (1) provided with its second plug (4) in the selected compartment;

- devices for loading the pellets (6) in columns (12) and means of loading various structural components (5) other than the retaining spring (7) and the second plug (4) are installed in the last compartment;

- at least one device for cleaning and possible means of checking contamination of the part of the cladding (2) exposed to contamination during loading of the pellets (6) are is installed in a preceding compartment;

- means of loading the retaining spring (7) and of fitting with tightening or not the second plug (4) in the open end (34) of the cladding (2) are installed in another preceding compartment;

- means necessary for carrying out possible additional welding and/or pressurisation operations can be installed in the same compartment or in yet another compartment;

- means of checking contamination and possibly of cleaning of the parts of the rod (1) exposed to contamination during the preceding operations are installed in the first or second compartment;

~~—means of ventilating the enclosure (10), its compartments and any enclosures installed therein, and gas supply means, are installed in order to maintain within the enclosure (10) at~~
there is a depression compared with the atmosphere of the room; and are arranged to provide

~~- each compartment contains a selection of gas for each compartment, chosen from~~
amongst the group formed by: air, nitrogen, helium, argon, vacuum; and

~~- stepping of the depressions of within the compartments are stepped —for the purposes of organising the direction of any leaks and contributing towards the stepping of the contaminations—from the a weakest depression in the first compartment to the a strongest depression in the last compartment, so as to organize the direction of any leak and contribute towards a stepped contamination level.~~

10. (currently amended): Device according to Claim 9, characterised in that it comprises a device (14) for presentation, centring and alignment of the pellets (6) with a view to their loading into the cladding (2), itself

- consisting of a fixed metal component (14) with a channel (42) passing through it – the dimensions of the input (44) of which are chosen for accepting an off-centring of the pellets (6) in relation to the axis of the cladding (2), and the bottom of which has a V-shaped profile in a continuous ramp and intersecting with a cylindrical output (48) with the diameter of the pellets (6) – and provided with a cylindrical chamber (49) with the diameter of the cladding (2) and centred on the cylindrical output (48) of the channel;

- having dimensions and tolerances adapted to the dimensions of said pellets (6) and cladding (2), and such that the diameter of the cylindrical output (48) of the channel is smaller

than the internal diameter of the cladding ~~(2)~~, for the purposes of masking the end of the cladding ~~(2)~~ from the pellets ~~(6)~~;

- optionally having longitudinal and/or transverse clearances and nozzles for blowing a gas in a direction opposite to the direction of loading and/or sucking up the dust and chips.

11. (currently amended): Device according to Claim 10, characterised in that it comprises, for loading of the pellets ~~(6)~~ and structural components, a pushing mechanism ~~(50)~~ with sensitive drive, having

- on the one hand axial driving by a set of rollers ~~(56)~~ equipped with a force limiting device ~~(54)~~ with low inertia and driven by a motor ~~(52)~~, the force of which is limited according to the depth of introduction of the pushing device ~~(53)~~ and the order ~~(24)~~ of the column of pellets ~~(6)~~ in the process of being loaded into the same cladding ~~(2)~~; and

- on the other hand a hollow rod ~~(53)~~ of low mass and adapted length, so that the depth of introduction of the last pellet ~~(6)~~ of a column loaded into the cladding ~~(2)~~ is equal to at least the length of the next column to be loaded into the same cladding ~~(2)~~.

12. (currently amended): Device according to Claim 11, characterised in that it has at least one device for dry or slightly moist cleaning of the parts of the cladding ~~(2)~~ or respectively of the rod ~~(1)~~ exposed to contamination.

13. (currently amended): Device according to Claim 12, characterised in that at least one of the cleaning devices comprises a system with strips, of woven or non-woven material, rubbing when dry or after slight moistening on the parts of said cladding ~~(2)~~ or respectively of the rod ~~(1)~~ which have been exposed to contamination.

14. (currently amended): Device according to Claim 13, characterised in that the containment enclosure ~~(10)~~ consists of four compartments, of which

- the fourth and last ~~(IV)~~ comprises the devices for loading the pellets ~~(6)~~ in columns ~~(12)~~ and the means for loading various structural components, other than the spring ~~(7)~~ and the second plug ~~(4)~~; and

- the third ~~(III)~~ comprises means for cleaning the part of the cladding ~~(2)~~ exposed to contamination during loading;

~~the second (II) comprises means for loading the retaining spring (7) and fitting with tightening or not the second plug (4);~~

~~the first input/output compartment (I) comprises contamination checking means and possibly a cleaning device.~~

15. (currently amended): Device according to Claim 14, characterised in that the sealed passages ~~(24)~~ between compartments comprise at least

- a valve ~~(26)~~ which can either be fully closed or leave a complete passage open without contact for a cladding ~~(2)~~ or respectively a rod ~~(1)~~;

- a sealing joint member ~~(28)~~ arranged to either leave a complete passage open without contact for a cladding ~~(2)~~ or form a seal around a cladding ~~(2)~~ which is either stopped at this place or in relative motion rotation-wise or translation-wise; and

- a device for pumping out the gas confined in the volume contained between the valve ~~(26)~~ and the sealing member ~~(28)~~, both closed, and for possible filling of this same volume with another gas.

16. (original): Device according to Claim 15, characterised in that at least one gas supply device is arranged for supplying said compartments – and any chambers installed therein – with various gases chosen from amongst the group air, N₂, Ar, He and vacuum.

17. (currently amended): Device according to Claim 16, characterised in that it comprises a system for distributing helium, in either open circuit or closed circuit in recycling mode or else a combination of the two, intended to supply the compartments for loading the pellets ~~(6)~~, for subsequent cleaning and for fitting of the second plug ~~(4)~~.

18. (currently amended): Device according to Claim 16, characterised in that the last compartment intended for loading of the pellets ~~(6)~~ comprises means for loading the pellets ~~(6)~~ into the cladding ~~(2)~~ under vacuum.

19. (currently amended): Device according to Claim 17, characterised in that the second compartment ~~comprising the fitting means also~~ comprises a device for circumferential welding of the second plug ~~(4)~~ to the cladding ~~(2)~~, ~~when said plug is mounted without tightening in the cladding (2).~~

20. (currently amended): Device according to claim 18, characterised in that the second compartment ~~comprising the fitting means also~~ comprises a device for circumferential welding of the second plug ~~(4)~~ to the cladding ~~(2)~~, ~~when said plug is mounted without tightening in the cladding (2).~~